

PROXON PROMASTIC R

PROXON PROMASTIC R

primer is a solvent-based, rubber-modified synthetic chlorinated primer.

Cold-applied, it's specifically designed as a primer for pipe coating applications.



What

PROXON PROMASTIC R primer is a solvent-based, rubber-modified, synthetic chlorinated primer. It is cold-applied and specially designed as a primer for pipe coating applications, offering reliable performance and durability in demanding environments.

Why?

- Single component, cold-applied
- Ready-to-use, easy application
- Economical and effective
- Penetrates porous substrates
- Excellent adherence quality
- Flexible with elasticity

How to use?

The substrate must be dry, clean, and free of grease, oil, tar, & loose particles. Step 1: Stir **PROXON PROMASTIC R** primer before application. Step 2: Apply a thin coat using a brush or spray and let it dry for 15–30 minutes. Step 3: Apply the coating membrane directly to the primed substrate.

Where?

PROXON PROMASTIC R primer is ideal for surface preparation in pipe coating and wrapping applications. It also serves as an anti-corrosive primer, offering excellent substrate protection and enhancing durability.

PROXON PROMASTIC R

Technical Information

Properties	Test method	Specification
Viscosity @ 25 ° C, sec	Ford cup No:4	35 – 60
Volatile Matter, by mass, %	IS 10221	Max 75
Drying Time, Min	Measurement	15–30
Flash Point ° C	ASTM D 92	>23

Packing

20 Ltr Container.

Coverage

PROXON PROMASTIC R covers 3.5–4.5 m²/Ltr. Coverage may vary based on surface condition, temperature, wind velocity, applicator skill, porosity, and substrate quality.

Storage

PROXON PROMASTIC R has a 12-month shelf life from the manufacturing date when stored in its unopened, original, dry condition. Keep away from fire or heated surfaces.

Safety Measures

Wear gloves, safety shoes, and goggles when handling **PROXON PROMASTIC R**. If eyes or mouth are affected, wash with water and seek medical help. Keep away from fire/heat. Avoid prolonged exposure in closed areas.

A Cold-applied, Rubber-modified Chlorinated Primer

PROXON PROMASTIC R

MANUFACTURING & MARKETING BY:

PROXON PRIVATE LIMITED

Corporate Office : #2/3, Sakthi Nagar Main Road, Arumbakkam,
Chennai-600 106, TamilNadu, India | **MOB :** +91 89259 62014

Website : www.proxon.in | info@proxon.in



Product Use Advisory : The technical information and advice provided are based on current scientific and practical knowledge. As this is general information, no warranty is given on product suitability for specific applications. Users must verify product suitability for their intended use and application.