

PROXON SILVER

PROXON SILVER is a low-odor, cold-applied, solvent-based aluminium paint that provides a durable, high-quality aluminum finish to surfaces.



What

PROXON SILVER is a corrosion-resistant, waterproof paint with an aluminium finish. It is made from oxidized bitumen, volatile solvents & a specially engineered aluminium compound, providing excellent protection & durability for various surfaces.

Why?

- One component, cold-applied solution
- Ready-to-use and economical
- Easy application for convenience
- Penetrates porous substrates effectively
- Adheres excellently to surfaces
- Offers flexibility and elasticity

Usage

PROXON SILVER is ideal for metal or concrete substrates, providing an aluminium finish for waterproofed surfaces, structures, lamp posts, telephone poles, electrical poles, and similar applications, ensuring durability and aesthetic appeal.

How to use?

- Ensure the surface is clean
- Stir **PROXON SILVER** thoroughly
- Apply a thin coat
- Allow 1-2 hours drying
- Apply second Reflex coat
- Clean tools with solvent

PROXON SILVER

Coverage

Coverage of **PROXON SILVER** paint on metal substrate is 6 – 10m² / Kg / Coat & on concrete substrate is 2.5 – 3 m² / Kg / Coat. Coverage may vary depending upon the surface condition, temperature, wind velocity, applicator's skill, surface porosity and quality of substrate.

Shelf Life

PROXON SILVER paint has a 12-month shelf life from the manufacturing date when

stored unopened in its original, sealed, and dry condition. Keep it away from fire or heat sources.

Safety

Wear gloves, safety shoes, and goggles when handling **PROXON PROSILVER** paint. If contact occurs, rinse thoroughly with water and seek medical attention. Refer to the MSDS before use; available upon request.

Physical Properties

Consistency	Smooth, Uniform, Brush-able
DFT / coat	30 to 40 Micron
Finish	Silver
Drying Time, hr	5
Specific Gravity	0.96
Packing	20 Kg Container

Technical Information

PROPERTY	Test method	Specification
Density, g/cm ³ @ 30 ° C	Measurement	1-1.2
Viscosity @ 25 ° C, cps	Brookfield Viscometer	150 – 200
Drying Time, Hrs		1-2

Cold-applied, Low-odor Aluminium Paint

PROXON SILVER

MANUFACTURING & MARKETING BY:
PROXON PRIVATE LIMITED

Corporate Office : #2/3, Sakthi Nagar Main Road, Arumbakkam,
Chennai-600 106, TamilNadu, India | **MOB :** +91 89259 62014

Website : www.proxon.in | info@proxon.in



Product Use Advisory : The technical information and advice provided are based on current scientific and practical knowledge. As this is general information, no warranty is given on product suitability for specific applications. Users must verify product suitability for their intended use and application.